

High frequency solar inverter

PV1800 VPM Series (1.2KW-5KW)






Features

- Pure sine wave output
- Smart LCD setting (Working modes, Charge Current, Charge Voltage, etc).
- Built in MPPT 60A/80A solar charge controller
- Combining solar system, AC utility, and battery power source to supply continuous power
- Overload, short circuit and Deep discharge protection
- Cold start function
- Support USB, RS485 monitoring function
- WIFI remote monitoring (optional)
- Compatible to generator
- Support parallel operation up to 3 units (available for 3KW-5KW 48V)

Introduction

This is a multi-function inverter/charger, combining functions of inverter, MPPT 60A/80A solar charger and battery charger to offer uninterruptible power support with portable size. Its comprehensive LCD display offers user-configurable and easy-accessible button operation such as battery charging current, AC/solar charger priority, and acceptable input voltage based on different applications.

Back panel printing description



1. LCD Display

2. Status Indicator

3. Charging Indicator

4. Fault Indicator

5. Function Buttons

6. AC input

7. AC output

8. Circuit breaker

9. Battery input

10. PV input

11. Power on/off switch

12. RS-485 Communication port


13. USB

14. Dry contact

15. USB wifi

[PV1800 VPM 2-3K]

Solar system connection



Specification

MODEL		PV18-1212 VPM	PV18-2024 VPM	PV18-3024 VPM	PV18-3048 VPM	PV18-4048 VPM	PV18-5048 VPM
Default Battery System Voltage		12VDC	24VDC		48VDC		
INVERTER OUTPUT	Rated Power	1200VA / 1200W	2000VA / 2000W	3000VA / 3000W	3000VA / 3000W	4000VA / 4000W	5000VA / 5000W
	Surge Power	2000VA	4000VA	6000VA	6000VA	8000VA	10000VA
	Waveform	Pure sine wave					
	AC Voltage Regulation (Batt.Mode)	220VAC~240VAC(Setting)					
	Inverter Efficiency(Peak)	90%~93%					
	Transfer Time	10ms(UPS / VDE4105) / 20ms(APL)					
AC INPUT	Voltage	230VAC					
	Selectable Voltage Range	170~280VAC(UPS) / 90~280VAC(APL) / 184~253VAC(VDE)					
	Frequency Range	50Hz / 60Hz (Auto sensing)					
BATTERY	Normal voltage	12VDC	24VDC		48VDC		
	Floating Charge Voltage	13.7VDC	27.4VDC		54.8VDC		
	Overcharge Protection	15VDC	30VDC		60VDC		
SOLAR CHARGER & AC CHARGER	Maximum PV Array Open Circuit Voltage	105VDC	145VDC		145VDC		
	PV Array MPPT Voltage Range	15~105VDC	30~120VDC		60~130VDC		
	Standby Power Consumption	2W					
	Maximum PV Array Power	720W	1500W		4000W		
	Maximum Solar Charge Current	60A			80A		
	Maximum Efficiency	98%					
	Maximum AC Charge Current	10A or 20A	20A or 30A		60A		
	Maximum Charge Current	70A	80A		140A		
MECHANICAL SPECIFICATIONS	Machine Dimension (W*H*D)	224*337*98mm	290*342*125mm		297.5*468*125mm		
	Package Dimension (W*H*D)	/	/		/		
	G.W (kg)	/	/		/		
	N.W (kg)	/	/		/		
OTHER	Humidity	5% to 95% Relativ Humidity (Non-condensing)					
	Operating Temperature	0°C~50°C					
	Storage Temperature	-15°C -60°C					