


KSTAR

BLUE-G THREE PHASE SERIES

BluE-3K-M1 / BluE-3.6K-M1 / BluE-4K-M1 /
BluE-5K-M1 / BluE-6K-M1 / BluE-8K-M1 /
BluE-10K-M1 / BluE-12K-M1 / BluE-15K-M1
/ BluE-17K-M1 / BluE-20K-M1 / BluE-22K-M1
/ BluE-23K-M1 / BluE-25K-M1



PV On-Grid String Inverter



Max. PV voltage up to 1100V
Type II DC /AC SPD



Compatible for big capacity PV panel
WiFi / 4G Plug optional



DC/AC ratio up to 2
IP66 protection



High efficiency up to 98.6%
Smaller and lighter

MODEL	BluE-3KT-M1	BluE-3.6KT-M1	BluE-4KT-M1	BluE-5KT-M1	BluE-6KT-M1
Input(DC)					
Max. DC Voltage	1100V	1100V	1100V	1100V	1100V
Nominal Voltage	620V	620V	620V	620V	620V
Start Voltage	180V	180V	180V	180V	180V
MPPT Voltage Range	140 V~1,000 V	140 V~1,000 V	140 V~1,000 V	140 V~1,000 V	140 V~1,000 V
Number of MPPT Tracker	2	2	2	2	2
Strings Per MPPT Tracker	1	1	1	1	1
Max. Input Current Per MPPT	15A	15A	15A	15A	15A
Max. Short-circuit Current Per MPPT	20A	20A	20A	20A	20A
Output(AC)					
Nominal AC Output Power	3000W	3600W	4000W	5000W	6000W
Maximum AC Output Power	3300VA	3960VA	4400VA	5500VA	6600VA
Nominal AC Voltage	400V 3L+N				
AC Grid Frequency Range	50 / 60Hz(±5Hz)				
Maximum Output Current	4.8A	5.8A	6.4A	8.0A	9.6A
Power Factor(Φ)	0.8leading-0.8lagging				
THDi	3%				
Efficiency					
Max. Efficiency	98.4%	98.4%	98.4%	98.4%	98.4%
Euro Efficiency	97.5%	97.5%	97.5%	97.5%	97.5%
Protection devices					
DC Switch	Yes				
Output Over Current	Yes				
Anti-islanding Protection	Yes				
DC Reverse Polarity Protection	Yes				
String Fault Detection	Yes				
AC/DC Surge Protection	DC: Type II / AC: Type III / Type II Optional				
Insulation Detection	Yes				
AC Short Circuit Protection	Yes				
General Specifications					
Dimensions W x H x D	380x483x161mm				
Weight	<17kg				
Operating Temperature Range	-25°C~+60°C				
Cooling Type	Natural cooling				
Max. Operation Altitude	4000m				
Max. Operation Humidity	0-100%(No condensation)				
AC Output Terminal Type	Connector				
IP Class	IP66				
Topology	Transformer-less				
Communication	RS485/Wifi/4G				
Display	LCD				
Certification & Standard	EN/IEC62109-1/2 ; IEC/EN61000-6-2;IEC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727; EN50549-1;AS 4777.2;VDE-AR-N-4105;VDE 0126-1-1;CEIO-21;G98;G99;C10/C11;NB/T32004-2018 ; GB/T19964-2012				

* Specifications subject to change without prior notice.

MODEL	BluE-8KT-M1	BluE-10KT-M1	BluE-12KT-M1	BluE-15KT-M1	BluE-17KT-M1
Input(DC)					
Max. DC Voltage	1100V	1100V	1100V	1100V	1100V
Nominal Voltage	620V	620V	620V	620V	620V
Start Voltage	180V	180V	180V	180V	180V
MPPT Voltage Range	140 V~1,000 V	140 V~1,000 V	140 V~1,000 V	140 V~1,000 V	140 V~1,000 V
Number of MPPT Tracker	2	2	2	2	2
Strings Per MPPT Tracker	1	1	1	2	2
Max. Input Current Per MPPT	15A	15A	15A	30A	30A
Max. Short-circuit Current Per MPPT	20A	20A	20A	40A	40A
Output(AC)					
Nominal AC Output Power	8000W	10000W	12000W	15000W	17000W
Maximum AC Output Power	8800VA	11000VA	13200VA	16500VA	18700VA
Nominal AC Voltage	400V 3L+N				
AC Grid Frequency Range	50 / 60Hz(±5Hz)				
Maximum Output Current	12.8A	16.0A	19.2A	23.9A	27.1A
Power Factor(Φ)	0.8leading-0.8lagging				
THDi	3%				
Efficiency					
Max. Efficiency	98.6%	98.6%	98.6%	98.6%	98.6%
Euro Efficiency	98.0%	98.1%	98.1%	98.2%	98.3%
Protection devices					
DC Switch	Yes				
Output Over Current	Yes				
Anti-islanding Protection	Yes				
DC Reverse Polarity Protection	Yes				
String Fault Detection	Yes				
AC/DC Surge Protection	DC: Type II / AC: Type III / Type II Optional				
Insulation Detection	Yes				
AC Short Circuit Protection	Yes				
General Specifications					
Dimensions W x H x D	380x483x161mm				
Weight	<17kg				
Operating Temperature Range	-25°C~+60°C				
Cooling Type	Natural cooling				
Max. Operation Altitude	4000m				
Max. Operation Humidity	0-100%(No condensation)				
AC Output Terminal Type	Connector				
IP Class	IP66				
Topology	Transformer-less				
Communication	RS485/Wifi/4G				
Display	LCD				
Certification & Standard	EN/IEC62109-1/2 ; IEC/EN61000-6-2;IEC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727; EN50549-1;AS 4777.2;VDE-AR-N-4105;VDE 0126-1-1;CEI0-21;G98;G99;C10/C11;NB/T32004-2018 ; GB/T19964-2012				

* Specifications subject to change without prior notice.

KSTAR

Stock code: 002518

Add: 4/F, No.1 Bldg.Software Park, Keji C. Rd. 2nd, Hi-Tech Industrial Zone, Shenzhen 518057, P.R.China

Website: www.kstar.com E-mail: sales@kstar.com

MODEL	BluE-20KT-M1	BluE-22KT-M1	BluE-23KT-M1	BluE-25KT-M1
Input(DC)				
Max. DC Voltage	1100V	1100V	1100V	1100V
Nominal Voltage	620V	620V	620V	620V
Start Voltage	180V	180V	180V	180V
MPPT Voltage Range	140 V~1,000V	140 V~1,000V	140 V~1,000V	140 V~1,000V
Number of MPPT Tracker	2	2	2	2
Strings Per MPPT Tracker	2	2	2	2
Max. Input Current Per MPPT	30A	30A	30A	30A
Max. Short-circuit Current Per MPPT	40A	40A	40A	40A
Output(AC)				
Nominal AC Output Power	20000W	22000W	23000W	25000W
Maximum AC Output Power	22000VA	24200VA	25300VA	27500VA
Nominal AC Voltage	400V 3L+N			
AC Grid Frequency Range	50Hz / 60Hz(±5Hz)			
Maximum Output Current	31.9A	35.1A	36.7A	39.9A
Power Factor(Φ)	0.8leading-0.8lagging			
THDi	3%			
Efficiency				
Max. Efficiency	98.6%	98.6%	98.6%	98.6%
Euro Efficiency	98.3%	98.3%	98.3%	98.3%
Protection devices				
DC Switch	Yes			
Output Over Current	Yes			
Anti-islanding Protection	Yes			
DC Reverse Polarity Protection	Yes			
String Fault Detection	Yes			
AC/DC Surge Protection	DC: Type II / AC: Type III / Type II Optional			
Insulation Detection	Yes			
AC Short Circuit Protection	Yes			
General Specifications				
Dimensions W x H x D	380x483x193mm			
Weight	25kg			
Operating Temperature Range	-25°C~+60°C			
Cooling Type	Fan Cooling			
Max. Operation Altitude	4000m			
Max. Operation Humidity	0-100%(No Condensation)			
AC Output Terminal Type	Connector			
IP Class	IP66			
Topology	Transformer-less			
Communication	RS485/Wifi/4G			
Display	LCD			
Certification & Standard	EN/IEC62109-1/2 ; IEC/EN61000-6-2;IEC/EN61000-6-4;IEC61683;IEC60068;IEC60529;IEC62116;IEC61727; EN50549-1;AS 4777.2;VDE-AR-N-4105;VDE 0126-1-1;CEI0-21;G98;G99;C10/C11;NB/T32004-2018 ; GB/T19964-2012			

* Specifications subject to change without prior notice.