



### Application

Surge protective device, protect against lightning surge voltages in solar system (photovoltaic power supply system). These units must be installed in parallel on the dc networks to be protected and provide common and different models protection. Its installed location are recommended at both ends of the dc power supply line (solar panel side and inverter/converter side), especially if the line routing is external and long. High energy MOVs equipped with specific thermal disconnectors and related failure indicators.

### Specifications

SNSPD-PV Series Surge Protector	SNSPD-PV							
PVDC - specific	EN50539-11							
Pole	2P	2P	2P	2P	3P	3P	3P(COSTOMIZED)	
Electrical parameter								
Classified test	II	II	II	II	II	II	II	
Uoc max (VDC )	500	600	800	1000	1000	1000	1500	1500
1	500	600	800	1000	1000	1000	1500	1500
In (8 /20 )us ( kA )	20	20	20	20	20	20	20	20
Ima x (8 /20 )us ( kA )	40	40	40	40	40	40	40	40
Up ( kV )	2.8	2.8	2.8	3.2	3.2	3.2	5.0	5.0

### Remote Signal Contact

Remote signal contact	Maximum working voltage (V)	250VAC/30VDC	250VAC /30VDC
-	Maximum working current (A ) IA ( 250 V /AC )IA ( 250V/AC )	IA ( 250V/AC )	IA (250V /AC )
	IA ( 30 V DC )	IA (30V/AC )	IA (30V /AC )

### Installation and Dimensions

Wiring capacity(mm2)	Hard wire	4~25	4~25
	Flexible wire	4~16	4~16
Stripping length(mm )		10	10
Terminals crcwa		M5	M5
Torque (Nm )	Main circuit	3.5	3.5
	Remote signal contact	0.25	0.25
Protection class	All profile	IP40	IP40
	Connection port	IP20	IP20
Installation environment	No obvious shock and vibration		
Altitude (m)		≤2000	≤2000
Working Temperature		-30°C ~ +70°C	-30°C ~ +70°C
Relative humidity		30%~90 %	30%~90 %
How to install	Installed with H 35-7.5/DIN35 steel mounting rail		
Size (mm ) (W x H x L )	W	36	54
	H	90	90
	L	67.6	67.6
Weight (kg )		0.24	0.36